

PRODUCT-DETAILS

## ACS55-01N-02A2-1

## ACS55-01N-02A2-1, 120VAC, Pn 0.5HP, I2LD, 2.2A, IP20

General Information	
Global Commercial Alias	ACS55-01N-02A2-1
Product ID	68884811
ABB Type Designation	ACS55-01N-02A2-1
EAN	6438177015352
Catalog Description	ACS55-01N-02A2-1, 120VAC, Pn 0.5HP, I2LD, 2.2A, IP20
Long Description	The ACS55 micro drives can control a variety of simple applications such as automatic gate, solar trackers, fans, conveyors, treadmills and whirlpool baths in both commercial and domestic environments. It fits perfectly even in small spaces and guarantee reliable operation for your machines. It can be also integrated easily into existing panels, replacing contactors and motor starters. Its interface with DIP switches and trimmers is exceptionally intuitive and configuring drives in volume is easy with an optional DriveConfig kit.

Ordering	
Country of Origin	China (CN)
Customs Tariff Number	85044080
Invoice Description	ACS55-01N-02A2-1, 120VAC, Pn 0.5HP, I2LD, 2.2A, IP20
Made To Order	No
Minimum Order Quantity	1 EA
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

Dimensions	
Product Net Weight	0.68 kg
Product Net Height	6.69 in
Product Net Length	5.04 in
Product Net Width	1.77 in
Package Level 1 Units	0 carton

Technical	
Number of Phases	3
Degree of Protection	IP20
Frequency (f)	50/60 Hz
Input Voltage (U <sub>in</sub> )	110 120 V

39122001

Mounting Type	Rail-mounted
Output Current, Normal Use	2.2 A
Output Power, Light- Overload Use	0.5 Hp
Output Power, Normal	0.5 Hp
Use	·
· ·	
·	<u> </u>

Environme	antal

Classifications

UNSPSC

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

## Categories

 $\mathsf{Drives} \to \mathsf{Low} \ \mathsf{voltage} \ \mathsf{AC} \ \mathsf{drives} \to \mathsf{Micro} \ \mathsf{drives} \to \mathsf{ACS55} \ \mathsf{-} \ \mathsf{Compact} \ \mathsf{Micro} \ \mathsf{Drive}$